



MODEL-900 SERIES DIMENSIONS

	X-904	X-904-6	X-904-8	X-904-10	X-904-12
A	20 FT.	20 FT.	20 FT.	b.20 FT.	b.20 FT.
B	67 INS.	79.5 INS.	79.5 INS.	88 INS.	95 INS.
C	62 INS.	74.5 INS.	74.5 INS.	83 INS.	90 INS.
D	7 FT.	7 FT.	7 FT.	7 FT.	7 FT.
E	8 FT.	8 FT.	8 FT.	8 FT.	8 FT.
F	39 FT.	39 FT.	39 FT.	39 FT.	39 FT.
G	74 INS.	89 INS.	89 INS.	100 INS.	107 INS.
H	85INS.	100 INS.	100 INS.	1111 INS.	118 INS.
I	d. 11 FT.	d. 11 FT.	d. 11 FT.	d. 11 FT.	d. 11 FT.

NOTE: NET WT 400 LBS.

a. STABILIZER UN-EXTENDED LENGTH

b. 5/8" CABLE STINGER ASSEMBLY WITH 5/8" X 22' 2" SAFETY CABLE WITH A 3/4" 7' 4-LEG SPREADER -- SWLL OF 3.8 TONS IN A 60 DEGREE ANGLE



BILLY PUGH CO., INC.

BILLY PUGH CO., INC.
P.O. BOX 802 CORPUS CHRISTI TX 7840.

SCALE: APPROVED BY: DRAWN BY:

SCALE NOV. 2006 SCALE:

THE 900 SERIES PERSONNEL TRANSFER
ARE POWDER COATED

DRAWING NUMBER: