



适用范围 The scope of application:

适用于各类船舶之间白昼信号联络之用。

Applied to daylight signal communication between the ships.

产品特点 Products characteristic:

- 1、壳体采用优质铸铝模压成型、机械闪光装置
- 2、重量轻，操作及携带方便

1. With good quality cast aluminum shell and mechanical flash device.
2. Light ,convenient to operate and bring.

采用标准 Adopt standard:

符合《MS.C.95(72)决议》和JISF8456-1996

Conform to MS.C.95(72) DECISION and JISF8456-1996

主要技术参数 Main technical parameter

白昼信号灯Daylight Signal Light	CXD8
电压Voltage / 功率Power	24V / 60W
灯座Lamp holder	G6.35
插头Plug	25M-4A四插Four pin
防护等级Protection class	IP44
电缆外径Cable outside diameter	Φ9.5
重量Weight	2.6kg
充电器Charger	CXD8-CDX
输入Input	AC110V/60Hz、AC220V/50Hz/60Hz
输出Output	AC24V、AC12V
使用温度Temperature	-25℃—45℃
插座Socket	四插Four pin 25M-4B / 三插Three pin 25M-3B
防护等级Protection class	IP20
重量Weight	3.6kg
蓄电池Battery	CXD8-XDX
容量Capacity	7Ah
充电电压Charge voltage	27.8V/13.9V
放电终止电压Discharge stop voltage	24V/12V
使用温度Temperature	-25℃~45℃
插座Socket	四插four pin 25M-4B
防护等级Protection class	IP20
重量Weight	4.0kg