

抛投式气胀救生筏 A 型

Throwing inflatable liferaft Type A

上海存宏船舶救生设备有限公司
SHANGHAI CUN HONG MARINE LIFESAVING APPLIANCE CO.,LTD.



适用范围: 国际航行船舶上使用

产品标准: 符合中华人民共和国船舶检验局《船舶与海上设施法定检验规则》“国际航行海船法定检验技术规范(2011)”和 SOLAS 74/96 修正案及 LSA, MSC.81(70)&MSC.48(66)&MSC.218(82)&MSC.293(87)&MSC.226(82)&MSC.295(87)&MSC.323(89) 的规定。

属具配备: A Pack 或 B Pack(短程国际航行船舶)。

充胀方式: 救生筏从船上投落后即可自动充胀展开。

最大存放高度: 安装高度距水面 18 ~ 36 米

证书: 中国船级社 CCS 型式认可证书

中国渔业船舶检验局 ZY 型式认可证书

德国劳氏船级社 (GL) EC 型式认可证书

【 Application 】 It is suitable for installing ships on international voyages.

【Product Standard】 It meets the requirements of 《Regulations for the Statutory Surveys of Ships and Offshore Installations 》“Technical Regulations for the Statutory Surveys of Sea-going Ships Engaged on International Voyages (2011)” of P.R.C. and SOLAS 74/96 Amendment, LSA and MSC.81 (70)&MSC.48(66) &MSC.218(82)&MSC.293(87)&MSC.226(82)&MSC.295(87)&MSC.323(89).

【Equipment Outfit】 A Pack or B Pack (Ships engaged on Short international voyage)

【Inflation method】 After throw-over from ship, the life-raft can be inflated and opened automatically.

【Max. Storage Height】 The installation height is 18~36m from water surface.

【 Certificate 】 China classification Society (CCS) Certificate of Type Approval
Register of Fishing Vessel of P.R.C (ZY) Certificate of Type Approval
Germanischer Lloyd (GL) EC Type Examination Certificate

型号 Model	定员 (mm) Capacity	长度 (mm) Length	宽度 (mm) Width	高度 (mm) Height	重量 Kg Weight A pack B pack		容器 Φ×L (cm) Container Size C type D type	
					A	B	C	D
CHF/DLR-A-6	6	2175	2175	1250	<90	<80	110×62	110×55
CHF/DLR-A-10	10	3245	2295	1300	<110	<90	115×69	110×60
CHF/DLR-A-12	12	3555	2455	1330	<125	<100	115×69	110×60
CHF/DLR-A-15	15	4110	2700	1350	<140	<110	120×71	110×66
CHF/DLR-A-16	16	4110	2700	1350	<150	<110	120×71	110×66
CHF/DLR-A-20	20	4585	3000	1570	<175	<135	140×74	110×72
CHF/DLR-A-25	25	5075	3325	1700	<200	<150	140×74	110×77