


HOISTING PAD EYE  
L 4" X 4" X 3/8" WITH 1" DIA. HOLE (TYP.) 3/8" WELDS ALL AROUND



TOE PLATE

TOP



3/4" #9 RAISED EXPANDED METAL LATH

3/16" FLOOR (BOTTOM)

7'



3/16" x 1" WELDS AT 12" O.C.  
BETWEEN BOTTOM ANGLE AND TOE PLATE. (TYP.)

- NOTES:**
1. ALL ROLLED STEEL PARTS SHALL BE MANUFACTURED FROM ASTM A-36 STEEL.
  2. ALL WELDS SHALL BE MADE WITH A233 6010 ELECTRODES.
  3. ALL MATING ANGLE MEMBERS SHALL RECEIVE FILLET WELDS ALONG ALL CORNERS FORMED BY THE MEMBERS.
  4. CORNER PADS, PAD EYES AND GUSSETT PLATES SHALL RECEIVE 3/8" FILLET WELD ALONG ALL CORNERS FORMED BY ANY TWO 3/8" THICK PLATES. THEY SHALL RECEIVE 3/16" WELDS ALONG ALL CORNERS FORMED BY 3/16" ANGLE FRAME MEMBERS. CORNER PADS SHALL RECEIVE 1/4" WELD ALONG THE CORNERS FORMED BY THE 3/8" PLATES AND THE FLAT SURFACES OF THE 2" ANGLES.

